

TRAMSPREAD

DIGESTATE AND SLURRY MANAGEMENT

NEW: SUFFOLK 12M COMBINATION DRIBBLE BAR



Tramsread's Suffolk dribble bars are available in sizes from 6m to 24m. The new Suffolk range 12m Combination dribble bar consists of a redesigned 12m dribble bar with the ability to carry a Tramsread 1000m random-wrap reeler. This makes it possible for the spreading tractor to carry a hose reeler in the front linkage and another on the back of the dribble bar when travelling between fields or jobs. Clear access to the tractor pick-up hitch also allows a Tramsread engine driven pump unit to be towed at the same time.

Although still incorporating Tramsread's premium build quality, the Combination dribble bar has a streamlined specification and is intended to offer a more cost-effective option where this type of machine is appropriate.



Typical standard specification includes:

- Ability to carry a Tramspread 1000m random wrap reeler
- Twin Alrena or Vogelsang macerators
- Full electronic control via in-cab control box
- Galvanised construction with breakback end sections
- Vertical folding allows access to tractor pick-up hitch
- Flow meter and NIR sensor ready
- Heavy-duty three-point linkage headstock
- 5" front-mounted heavy-duty swinging arm permitting U-turns
- 48 outlets at 25cm spacings



Options include:

- Purge outlet with spread nozzle
- Valves to reduce spread width
- Tramline shut-off valves



Copyright Tramspread Agri Ltd 2026 v3/26

• +44 (0)1449 766133 • info@tramspread.co.uk • www.tramspread.co.uk

Tramspread Agri Ltd, Buces Farm, Mendlesham, Suffolk, IP14 5NR, United Kingdom