

TRAMSPREAD

DIGESTATE AND SLURRY MANAGEMENT

NEW: SUFFOLK 24M DRIBBLE BAR



Tramspread's Suffolk dribble bars are available in sizes from 6m to 24m. The new 24m vertical-folding Suffolk dribble bar has been thoroughly field-tested over 18 months during which time it has successfully covered many hundreds of hectares. The completely new boom folds vertically, making it suitable for use with any make and model of appropriately sized tractor. It is close-coupled, meaning it is well-matched to tractors of around 150hp plus, just like the horizontal-folding version.

There has been no compromise in design, with heavy-duty, high-quality construction prioritised, making guy ropes unnecessary. The important ability to fold down to 18m, with shut-off taps, has been retained from the existing 18/24m dribble bar. Other premium features include break-back end sections, electrohydraulic controls using power-beyond and left/right variable boom geometry.



Typical standard specification includes:

- Folds down to 18m working width
- 2 x Vogelsang ECQ or Alrena distributors/macerators
- Dribble outlets spaced 300mm apart
- Left and right geometric control
- Full electro-hydraulic control via in-cab control box
- Galvanised, heavy-duty construction
- Breakback end sections
- Hydraulic vertical folding allowing access to the tractor pick-up hitch
- Heavy-duty three-point linkage headstock
- Auto transport safety latches with securing pins
- Designed to accept flowmeter and manure sensor
- Front-mounted 5" swinging arm permitting U-turns
- Easily tanker-mounted via linkage



Options include:

- Purge outlet with spread nozzle
- Valves to reduce spread width
- Tramline shut-off valves



Below: Ungalvanised prototype shown during extensive field-testing.



Copyright Tramspread Agri Ltd 2026 v3/26

• +44 (0)1449 766133 • info@tramspread.co.uk • www.tramspread.co.uk

Tramspread Agri Ltd, Buces Farm, Mendlesham, Suffolk, IP14 5NR, United Kingdom