

TRAMSPREAD

DIGESTATE AND SLURRY MANAGEMENT

SUFFOLK DRIBBLE BARS 6m-18m



Tramspread offers a comprehensive range of umbilical applicators engineered for exceptional performance and outstanding build quality. All models are fully galvanised for maximum durability and corrosion resistance, and feature hydraulic folding for safe, convenient transport and operation. The front-mounted swinging arm is unique to Tramspread and allows true U-turns on the headlands and full use of the tractor pick-up hitch when travelling on the road, meaning just one tractor is needed for a full umbilical application outfit.

The range includes single macerator models with working widths from 6m to 12m, and twin macerator versions in widths from 12m to 24m. They can be operated as umbilical applicators but can also be fitted to tankers. All models fold vertically and feature automatic transport latches with integrated safety locks. There has been no compromise in design, with heavy-duty and high-quality construction throughout. The robust frame design eliminates the need for guy ropes, ensuring strength, stability, and simplicity in the field.

SINGLE MACERATOR MODELS

Typical specification includes:

- 6m, 7m, 7.5m, 8m, 9m, 10m, 10.5m and 12m widths
- Vogelsang ECQ or Alrena distributor/macerator
- Dribble outlets 250mm apart (300mm on 12m model)
- Galvanised, heavy-duty construction
- Vertical folding allows access to tractor pick-up hitch
- Automatic transport safety latches with securing pins
- Designed to accept a flowmeter and manure sensor
- 3-point linkage with female A-frame
- Front-mounted 4" swinging arm permits U-turns
- Dribble bar easily removed from umbilical frame for tanker mounting (not 12m model)
- Purge outlet with spread nozzle (optional)



TWIN MACERATOR MODELS

Typical specification includes:

- 12m, 15m, 16m and 18m widths
- 2 x Vogelsang ECQ or Alrena distributors/macerators
- Dribble outlets 250mm apart
- Left and right geometric control
- Full electro-hydraulic control via in-cab control box
- Galvanised, heavy-duty construction
- Vertical folding allows access to tractor pick-up hitch
- Automatic transport safety latches with securing pins
- Designed to accept a flowmeter and manure sensor
- 3-point linkage with female A-frame
- Front-mounted 5" swinging arm permits U-turns
- Easily tanker-mounted via linkage
- Purge outlet with spread nozzle (optional)
- Valves to decrease spread width (optional)
- Tramline shut-off valves (optional)



Copyright Tramspread Agri Ltd 2026 v3/26

• +44 (0)1449 766133 • info@tramspread.co.uk • www.tramspread.co.uk

Tramspread Agri Ltd, Buces Farm, Mendlesham, Suffolk, IP14 5NR, United Kingdom